

CT 721



VISAGE

'Wood' Colour Impregnate

Design impregnate reflecting natural wood colours for outdoor and indoor use

CHARACTERISTICS

- ▶ available in 6 natural wood colours
- ▶ resistant to weather conditions
- ▶ exceptionally durable and resistant to soiling
- ▶ hydrophobic
- ▶ high stability of colour
- ▶ ready for use

SCOPE OF USE

The Ceresit CT 721 impregnate is used for executing a decorative layer with natural wood colours on the surface of the Ceresit CT 720 VISAGE 'Wood' Plaster, thin-layer mineral plasters, traditional plasters, concrete and gypsum surfaces. The CT 721 impregnate is one of the components used in the external thermal insulation composite Ceresit Ceretherm Visage system for building walls (ETICS) with application of expanded polystyrene boards. The material may be sprayed or applied with brush, roller or sponge. The impregnate features exceptional durability and resistance to soiling.

SURFACE PREPARATION

CT 721 may be used on carrying, dry surfaces, free of substances which decrease adhesion, such as grease, bitumens, dust):

- CT 720 VISAGE 'Wood' Plaster (age above 3 days),
- Thin-layer mineral plasters (age above 3 days),
- Cement and cement-lime plasters (age above 28 days), concrete (age above 3 months, moisture ≤ 4%),
- gypsum surface, e.g. decorative plasters (only inside buildings) with moisture below 1%.

Moisture pressure from the surface may result in plaster damage, therefore the rooms (places) exposed to permanent moistness should be provided with appropriate sealing layers.

APPLICATION

Before use, mix thoroughly the contents of the container. Additionally, make quick mixing movements during application. Do not use rusty containers or tools.



Apply the impregnant in at least two layers wet on wet. CT 721 may be sprayed or applied with brush, roller or sponge. Work on one surface should continue uninterrupted, with the impregnant of the same batch on each package, or mix the contents of the containers with different batches together. Thoroughly protect (e.g. with foil) the surfaces which are not to be painted, e.g. windows, doors. Cover shrubs, other plants, etc. Wash accidental stains immediately with plenty of water. Wash tools thoroughly with water right after use.

PLEASE NOTE

Application should be performed in dry conditions, at air and surface temperature from +5°C to +25°C and with relative air humidity below 80%. All data refer to temperature +20°C and relative air humidity 60%. Under other conditions, faster or slower hardening of material shall be taken into consideration. The impregnate plaster should be protected against rainfall until it is thoroughly hard. Use covers on scaffolding and building plinths. Do not mix product with other dyes and binding

material. Ventilate the rooms after application of impregnate until odour is no longer perceived, only then can the rooms be released for use. When material comes into contact with the eyes, rinse the eyes with plenty of water and seek medical advice. The product shall be stored in a place inaccessible for children.

RECOMMENDATIONS

Do not apply impregnate on walls with high insolation, protect the completed plaster against too fast drying. Opened packages shall be thoroughly closed, and their contents should be used as soon as possible.

This technical specification defines the scope of application of the material and recommended work procedures but it cannot replace professional experience of the contractor. Apart from the recommendations stated, work should be performed in accordance with building art and HS&E rules.

The manufacturer guarantees quality of the product, but cannot be held responsible for the conditions and method of its use. In case of doubts, run your own tests. This technical specification supersedes all earlier specifications.

STORAGE

Up to 12 months of the production date when stored in cool conditions and in the original, intact packages.

Protect against freezing! Protect against direct insolation.

PACKAGING

Plastic containers, 4 l.

TECHNICAL DATA

Base: selected silicone oligomers with addition of Teflon emulsion

Density: ca. 1.05 kg/dm³

Temperature of application: from +5 to +25°C

Open time: ca. 30 min.

Resistance to rain: after ca. 24 h

Assumed consumption: ca. 0.2 l/m²

Available colours:

Name CT 721
- Iberia Pine
- Norway Pine
- Bengal Teak
- Canada Walnut
- Congo Wenge
- Irish Oak

The product has the following reference documents:

- ETA in the system

Ceresit Ceretherm System	Visage
ETA	11/0395
Certificate	1488-CPD-0237/W
DoC.: Ceresit Ceretherm	WE-CC Visage 1/PL 15.02.2012

- The Technical Approval in the system

Ceresit Ceretherm System	Visage
TA	15-8399 /2011
Certificate	ITB-0416/Z
DoC.: Ceresit Ceretherm	Visage /1/11 01.07.2011

Apart from the information given here it is also important to observe the relevant guidelines and regulations of various organizations and trade associations as well as the respective standards. The aforementioned characteristics are based on practical experience and applied testing. Warranted properties and possible uses which go beyond those warranted in this information sheet require our written confirmation. All data given was obtained at an ambient and material temperature of +20 °C and 60 % relative air humidity unless specified otherwise. Please note that under other climatic conditions hardening can be accelerated or delayed.

The information contained herein, particularly recommendations for the handling and use of our products, is based on our professional experience. As materials and conditions may vary with each intended application, and thus are beyond our sphere of influence, we strongly recommend that in each case sufficient tests are conducted to check the suitability of our products for their intended use. Legal liability cannot be accepted on the basis of the contents of this data sheet or any verbal advice given, unless there is a case of wilful misconduct or gross negligence on our part. This technical data sheet supersedes all previous editions relevant to this product.



Henkel CEE GmbH
Erdbergstr. 29
A-1030 Vienna, Austria
www.henkel-cee.com